

# Guidance on the design, construction and testing of standard rail tank cars for the transport of chemicals in bulk



Issue 2  
May 2016



## INTRODUCTION

This document provides guidance on the design and construction of Rail Tank Cars (RTC's) and associated equipment commonly used for the transport in bulk of chemicals.

This document does NOT address the transport of solids or of products with specific requirements e.g. ethylene oxide, [chlorine](#), ammonia, etc.

The design and construction of RTC's must, as a minimum, be in compliance with the international regulations concerning the Carriage of Dangerous Goods by Rail (RID) (see <http://www.otif.org/en/dangerous-goods.html>) and with the European Directive 2010/35 on Transportable Pressure Equipment and other domestic regulations where applicable.

This guidance contains recommendations on top of what is already legally required.

The document is split into 2 columns:

- A. Liquids (with a focus on chemicals i.e. non-oil products)
- B. Gases (limited to liquefied flammable gases e.g. LPG, propane, butane, butadiene, propylene, etc. but excluding gases that have specific requirements such as ethylene oxide, chlorine, [ammonia](#), etc.)

Text that is common to both liquids and gases has been [shading in blue](#).

[New text with regard to the previous version is in blue](#).

This document replaces the previous version of the Cefic Guidelines issued in 2003.

### Disclaimer

This document is intended for information only and sets out guidance for the design, construction and testing of standard rail tank cars for the transport of chemicals in bulk. The information contained in this guidance is provided in good faith and, while it is accurate as far as the authors are aware, no representations or warranties are made with regard to its completeness. It is not intended to be a comprehensive guide to all the detailed aspects of rail transport equipment. No responsibility will be assumed by Cefic in relation to the information contained in this guidance.

<b>A. LIQUIDS</b>	<b>B. GASES (liquefied flammable)</b>
<p><b>CONTENTS</b></p> <ol style="list-style-type: none"> <li>1. Tank design and construction</li> <li>2. Equipment               <ol style="list-style-type: none"> <li>2.1 Manhole/manlid</li> <li>2.2 Pressure/vacuum relief</li> <li>2.3 Earthing</li> <li>2.4 Bottom discharge</li> <li>2.5 Top discharge</li> <li>2.6 Thermometers/manometers</li> <li>2.7 Controlled ventilation valves (Auto vent system)</li> </ol> </li> <li>3. Walkways/platforms</li> <li>4. Heating/insulation</li> <li>5. Underframe</li> <li>6. External painting/cladding</li> <li>7. Placarding and marking</li> <li>8. End protection</li> <li>9. Testing, inspection and certification</li> <li>10. Information/data to be submitted to the lessee (consignor) prior to putting into use RTC's</li> </ol>	<p><b>CONTENTS</b></p> <ol style="list-style-type: none"> <li>1. Tank design and construction</li> <li>2. Equipment               <ol style="list-style-type: none"> <li>2.1. Manhole/manlid</li> <li>2.2. Pressure relief</li> <li>2.3. Earthing</li> <li>2.4. Bottom discharge</li> <li>2.5. (Not applicable)</li> <li>2.6. Thermometers/manometers</li> <li>2.7. (Not applicable)</li> </ol> </li> <li>3. (Not applicable)</li> <li>4. Sunshield</li> <li>5. Underframe</li> <li>6. External painting</li> <li>7. Placarding and marking</li> <li>8. End protection</li> <li>9. Testing, inspection and certification</li> <li>10. Information/data to be submitted to the lessee (consignor) prior to putting into use RTC's</li> </ol>

<b>A. LIQUIDS</b>	<b>B. GASES (liquefied flammable)</b>
<p><b>1. TANK DESIGN AND CONSTRUCTION</b></p> <p>See RID requirements in RID 6.8.2.1</p> <p>Materials of tank construction, including coatings, valves, fittings, gaskets etc. shall be suitable for the specified products.</p> <p>For the shells of RTC's, which are intended for carrying different products, suitable stainless steel is recommended because of its resistance to a wide variety of chemicals.</p> <p>Compared with carbon steel, stainless steel might, in some cases, also have a positive influence on the product quality (e.g. colour) and leak-proofness of the bottom outlet/valve system of the RTC (no rust in seats of valves).</p> <p>The materials of shells (or protective linings), including all other components, which are in contact with the product, shall not contain substances liable to react dangerously with the product, or form dangerous compounds or degrade the material properties or quality of the carried products.</p> <p>New or treated stainless steel tanks must be properly pickled and passivated.</p> <p>For new tanks, all load bearing attachments shall have backing plates of a material compatible with the tank shell, thick enough to distribute incoming forces to an uncritical limit. Backing plates shall be fully welded to the shell and shall have all corners well rounded. Also a small boring is recommended for stress release.</p> <p>The tank must be designed for a calculation pressure as required by RID (see RID 6.8.2.1.14). It is recommended to have a design pressure of not less than 4 bar gauge.</p> <p>Atmospheric (vented) tanks even if allowed by national and international regulations, are not recommended.</p> <p>Vacuum relief valves shall not be fitted.</p> <p>Hermetically closed shells without vacuum relief valves shall be designed to withstand a minimum underpressure of 0.4 bar</p>	<p><b>1. TANK DESIGN AND CONSTRUCTION</b></p> <p>See RID requirements in RID 6.8.2.1 and 6.8.3.1</p> <p>Materials of tank construction, including coatings, valves, fittings, gaskets etc. shall be suitable for the specified products.</p> <p>The materials of shells (or protective linings), including all other components, which are in contact with the product, shall not contain substances liable to react dangerously with the product, or form dangerous compounds or degrade the material properties or quality of the carried products.</p> <p>For new tanks, all load bearing attachments shall have backing plates of a material compatible with the tank shell, thick enough to distribute incoming forces to an uncritical limit. Backing plates shall be fully welded to the shell and shall have all corners well rounded. Also a small boring is recommended for stress release.</p> <p>The tank must be designed for a calculation pressure as required by RID (see RID 4.3.3.2.5).</p> <p>Measures should be taken (see RID 6.8.2.1.7.) to protect the shells against the risk of deformation as a result of a negative internal pressure (vacuum). It is <b>highly</b> recommended that the tanks are designed to withstand an underpressure of 1bar.</p>

<b>A. LIQUIDS</b>	<b>B. GASES (liquefied flammable)</b>				
<p>Internal components such as baffle plates, internal reinforcements, internal ladders, shall not be fitted. Internal heating coils should be avoided if external heating is sufficient for the products carried.</p>					
<p>RTC's without underframe (“Selbsttragende Kesselwagen”) and RTC's, of which the tank is welded to the underframe over the full length, are not recommended.</p>	<p>RTC's without underframe (“Selbsttragende Kesselwagen”) and RTC's, of which the tank is welded to the underframe over the full length, are not recommended.</p>				
<p>Tanks must have drainage with flush welding seams at the surface of the bottom.</p>	<p>Tanks must have drainage with flush welding seams at the surface of the bottom.</p>				
<p>The tanks shall be designed to be explosion proof.</p>					
<p>The identification plate has to be properly fixed on the outside of the tank shell and all information has to be readable. The initial test data may not be overwritten by other test data (see RID 6.8.2.5.1 and EN 12561-1).</p>	<p>The identification plate has to be properly fixed on the outside of the tank shell and all information has to be readable. The initial test data may not be overwritten by other test data (see RID 6.8.2.5.1 and EN 12561-1).</p>				
<p><b>2. EQUIPMENT</b></p>	<p><b>2. EQUIPMENT</b></p>				
<p>See RID requirements in RID 6.8.2.1</p>	<p>See RID requirements in RID 6.8.3.2</p>				
<p>The following standards are recommended:</p>	<p>The following standards are recommended:</p>				
<table border="0"> <tr> <td data-bbox="183 1234 379 1256">EN 12561-1:2011</td> <td data-bbox="427 1234 735 1323">Marking of tank wagons for the carriage of dangerous goods</td> </tr> </table>	EN 12561-1:2011	Marking of tank wagons for the carriage of dangerous goods	<table border="0"> <tr> <td data-bbox="778 1234 975 1256">EN 12561-1:2011</td> <td data-bbox="1018 1234 1321 1323">Marking of tank wagons for the carriage of dangerous goods</td> </tr> </table>	EN 12561-1:2011	Marking of tank wagons for the carriage of dangerous goods
EN 12561-1:2011	Marking of tank wagons for the carriage of dangerous goods				
EN 12561-1:2011	Marking of tank wagons for the carriage of dangerous goods				
<table border="0"> <tr> <td data-bbox="183 1361 379 1384">EN 12561-2:2011</td> <td data-bbox="427 1361 735 1462">Bottom emptying devices for liquid products including vapour return</td> </tr> </table>	EN 12561-2:2011	Bottom emptying devices for liquid products including vapour return	<table border="0"> <tr> <td data-bbox="778 1361 975 1384">EN 12561-3:2011</td> <td data-bbox="1018 1361 1321 1462">Bottom filling and emptying devices for gases liquefied under pressure</td> </tr> </table>	EN 12561-3:2011	Bottom filling and emptying devices for gases liquefied under pressure
EN 12561-2:2011	Bottom emptying devices for liquid products including vapour return				
EN 12561-3:2011	Bottom filling and emptying devices for gases liquefied under pressure				
<table border="0"> <tr> <td data-bbox="183 1478 379 1500">EN 12561-4:2011</td> <td data-bbox="427 1478 735 1556">Top emptying and filling devices for liquid products</td> </tr> </table>	EN 12561-4:2011	Top emptying and filling devices for liquid products			
EN 12561-4:2011	Top emptying and filling devices for liquid products				
<table border="0"> <tr> <td data-bbox="183 1572 379 1594">EN 12561-5:2011</td> <td data-bbox="427 1572 735 1695">Devices for bottom emptying and top filling of liquid products</td> </tr> </table>	EN 12561-5:2011	Devices for bottom emptying and top filling of liquid products			
EN 12561-5:2011	Devices for bottom emptying and top filling of liquid products				
<table border="0"> <tr> <td data-bbox="183 1688 379 1711">EN 12561-6 :2011</td> <td data-bbox="427 1688 539 1711">Manholes</td> </tr> </table>	EN 12561-6 :2011	Manholes			
EN 12561-6 :2011	Manholes				
<table border="0"> <tr> <td data-bbox="183 1749 379 1771">EN 12561-7 :2011</td> <td data-bbox="427 1749 667 1771">Platforms and ladders</td> </tr> </table>	EN 12561-7 :2011	Platforms and ladders			
EN 12561-7 :2011	Platforms and ladders				
<table border="0"> <tr> <td data-bbox="183 1798 379 1821">EN 12561- 8:2011</td> <td data-bbox="427 1798 651 1821">Heating connections</td> </tr> </table>	EN 12561- 8:2011	Heating connections			
EN 12561- 8:2011	Heating connections				
<table border="0"> <tr> <td data-bbox="183 1859 347 1881">UIC leaflet 573</td> <td data-bbox="427 1859 735 1937">Technical conditions for the construction of tank wagons</td> </tr> </table>	UIC leaflet 573	Technical conditions for the construction of tank wagons	<table border="0"> <tr> <td data-bbox="778 1859 943 1881">UIC leaflet 573</td> <td data-bbox="1018 1859 1321 1937">Technical conditions for the construction of tank wagons</td> </tr> </table>	UIC leaflet 573	Technical conditions for the construction of tank wagons
UIC leaflet 573	Technical conditions for the construction of tank wagons				
UIC leaflet 573	Technical conditions for the construction of tank wagons				
<p>When one of these standards or leaflets is updated or replaced, the new version automatically applies.</p>	<p>When one of these standards or leaflets is updated</p>				

<b>A. LIQUIDS</b>	<b>B. GASES (liquefied flammable)</b>
<p><b>2.1 <u>Manhole/manlid</u></b></p> <p>There are no specific requirements in RID.</p> <p>Minimum diameter of the manhole must be 500 mm. Manlids with swing bolts and butterfly nuts have to comply with standard EN 12561-6:2011. For RTC's, not loaded via the manhole, a closure with nuts is recommended.</p> <p>The closing mechanism of the manlid shall be designed in such a way that internal pressure in the RTC can be released safely before the lid can be fully opened.</p> <p>The manlid must be secured properly when opened to less than 120 degrees. No obstacles shall prevent proper closure of the manlid.</p> <p>The manlid shall be fitted with a joint ring, which must be compatible with the product being carried.</p> <p>The manlid shall be gas tight, complying with RID 6.8.2.4.3.</p> <p>Fittings or other pieces of equipment on hinged manlid covers are not acceptable.</p> <p>Hinged manlids must be sealable.</p> <p><b>2.2 <u>Pressure/vacuum relief</u></b></p> <p>See RID requirements in RID 6.8.2.2 and 6.8.2.2.3</p> <p>Pressure/vacuum relief valves shall NOT be fitted if not required.</p> <p><b>2.3 <u>Earthing</u></b></p> <p>See RID requirements in 6.8.2.27 and section 5.5 of EN 12561-2.</p> <p>All parts of the tank wagon shall be bonded by equipotential connections and shall be capable of being electrically earthed.</p> <p>Earthing lugs must be available on both sides of the RTC, next to the outlet nozzle.</p> <p>In order to ensure proper bonding with the RTC, the earthing lug shall consist of a stainless steel plate of at least 40 mm x 80mm x 5mm , which must be</p>	<p>or replaced, the new version automatically applies.</p> <p><b>2.1 <u>Manhole/manlid</u></b></p> <p>There are no specific requirements in RID.</p> <p>Minimum diameter of the manhole must be 500 mm.</p> <p>The manlid shall be fitted with a joint ring, which must be compatible with the product being carried.</p> <p>The manlid shall be gas tight, complying with RID 6.8.2.4.3.</p> <p><b>2.2 <u>Pressure relief</u></b></p> <p>See RID requirements in RID 6.8.3.2.9</p> <p>Pressure relief valves shall NOT be fitted if not required.</p> <p><b>2.3 <u>Earthing</u></b></p> <p>See RID requirements in 6.8.2.27 and section 5.6 of EN 12561-3.</p> <p>All parts of the tank wagon shall be bonded by equipotential connections and shall be capable of being electrically earthed.</p> <p>Earthing lugs must be available on both sides of the RTC, next to the outlet nozzle.</p> <p>In order to ensure proper bonding with the RTC, the earthing lug shall consist of a stainless steel plate of at least 40 mm x 80mm x 5mm , which must be</p>

<b>A. LIQUIDS</b>	<b>B. GASES (liquefied flammable)</b>
welded directly onto equipment that is connected to the tank e.g. cradle for tee pipe, “Sattelleiste” (saddle bar) .	welded directly onto equipment that is connected to the tank e.g. cradle for tee pipe, “Sattelleiste” (saddle bar) .
The earthing plate may never be painted and must be properly marked with the international “earthing” symbol.	The earthing plate may never be painted and must be properly marked with the international “earthing” symbol.
For top loading / unloading, an extra earthing close to the top connections is recommended.	
<b>2.4 Bottom discharge</b>	<b>2.4 Bottom discharge</b>
<b>2.4.1 Bottom valves and operating mechanism</b>	<b>2.4.1 bottom valves and operating mechanism</b>
See RID requirements in RID 6.8.2.2	See RID requirements in RID 6.8.2.2.2 and 6.8.3.2.3
The tank shall be fitted with discharge pipework in the form of an outlet tee piece. The arm of the tee shall be directed to each side of the RTC and shall have a horizontal position.	The tank shall be fitted with discharge pipework in the form of two outlet tee pieces. The arms of the tee shall be directed to each side of the RTC and shall have a horizontal position.
<p>Each bottom-filling or bottom-discharge opening shall be equipped with at least three mutually independent closures, mounted in series, comprising:</p> <ul style="list-style-type: none"> <li>- An internal bottom-valve, i.e. a stop-valve mounted inside the shell or in a welded flange or companion flange;</li> <li>- An external stop-valve or equivalent device, one at the end of each pipe;</li> </ul>	<p>Each bottom-filling or bottom-discharge opening shall be equipped with at least three mutually independent closures, mounted in series, comprising:</p> <ul style="list-style-type: none"> <li>- An internal bottom-valve, i.e. a stop-valve mounted inside the shell or in a welded flange or companion flange;</li> <li>- An external stop-valve or equivalent device, one at the end of each pipe;</li> </ul>
- A closing device at the end of each pipe, which may be a screw threaded cap, a blind flange or an equivalent device.	- A closing device at the end of each pipe, which may be a screw threaded cap, a blind flange or an equivalent device.
The internal bottom-valve shall be operable from below. Its setting – open or closed – shall be capable of being verified. Internal bottom valve control devices shall be so designed as to prevent any unintended opening through impact or inadvertent act.	The internal bottom-valves (for liquid and gas phase) shall be operable from below. Its setting – open or closed – shall be capable of being verified. Internal bottom valve control devices shall be so designed as to prevent any unintended opening through impact or inadvertent act.
The internal bottom valve shall continue to be effective in the event of damage to the external control device.	The internal bottom valves shall continue to be effective in the event of damage to the external control device.
	Internal bottom valves shall be equipped with an instant-closing internal safety device which closes automatically in the event of an unintended movement of the shell. It shall also be possible to operate the closing device by remote control (see RID 6.8.3.2.3).

<b>A. LIQUIDS</b>	<b>B. GASES (liquefied flammable)</b>
<p>The bottom (DN 80 as a minimum) valve may be of a mechanical or hydraulic type provided the spring tension has a value of minimum 200 kg.</p> <p>A marking, which clearly indicates the operating of the bottom valve, must be visible near the operating mechanism.</p> <p>For RTC's which may carry different products, the gaskets of the bottom valve must be made out of PTFE or equivalent material, which must be compatible with the products carried. Wagons equipped with PTFE gaskets only should be marked with gasket class 1.</p> <p><b><u>2.4.2 Bottom discharge connections</u></b></p> <p>See RID requirements in RID 6.8.2.2.2</p> <p>The outlet piece shall be fitted at each end with an outlet (side) valve which may be a globe valve ("Schrägsitz"), plug valve or a ball valve.</p> <p>The types of the outlet valves must be the same on both sides.</p> <p>The discharge end of the outlet tee piece may terminate in a 5 ½" Whithworth screw-thread which is commonly used, and a screw (blank) cap and chain.</p> <p>Flanges may also be fitted.</p> <p>The use of dry disconnect couplings is recommended. However, dry disconnect couplings should not be used on tanks with crystallisable or highly viscous substances and also not on carbon steel tanks as a second closure.</p> <p>For bottom loading and unloading systems, dry disconnect couplings may be used as secondary closure instead of the outlet valve.</p> <p>If special couplings are not yet fitted, adequate spacing must be foreseen to connect these onto the outlet valves in a later stage. Adaptors of 5 ½ Withworth thread to dry disconnect couplings are NOT recommended. Dry disconnect couplings should be fitted to a flange.</p>	<p>The bottom valves (DN 80 for liquid phase and DN 80 or DN 50 for gas phase) may be of a mechanical, hydraulic type provided the spring tension has a value of minimum 200 kg.</p> <p>A label, which clearly indicates the operating instructions of the bottom valves must be attached to the tank near the operating mechanism.</p> <p><b><u>2.4.2 Bottom discharge connections</u></b></p> <p>See RID requirements in RID 6.8.2.2.2</p> <p>The outlets shall be fitted at each end with an outlet (side) valve which may be a globe valve ("Schrägsitz") plug valve or a ball valve. However, for carbon steel wagons, the use of globe valves is recommended.</p> <p>The types of the outlet valves must be the same on both sides.</p> <p>Types of connections currently used, and described below, are:</p> <ul style="list-style-type: none"> <li>- screw connections: e.g. WECO type</li> <li>- flange-type connections</li> <li>- dry disconnect couplings.</li> </ul> <p>When dry disconnect couplings are used, they should <b>only</b> be fitted as third closure in downstream direction of the outlet valve.</p>



## A. LIQUIDS

All screw caps shall be fabricated from stainless steel or the same material as the tank. Plastic caps are allowed but not recommended. The screw caps must be fitted with suitable full-flat-face gaskets.

The coupling device is connected to the connection pipe of the RTC with a flanged type connection.

## B. GASES (liquefied flammable)

The coupling device is connected to the connection pipe of the RTC with a flanged type connection.

### Screw-connections



WECO connection

In this case, the RTC is equipped with “female” half-joints, generally of 3” and 2” diameter for the liquid and gas phases. The half-joint has an external

thread which can be from the ACME or ISO type, and includes a gasket made of synthetic material compatible with the product to be carried. The joint is closed, during transport, by a threaded cap blocked by contact with the gasket.

In order to ensure that the coupling has not been removed for unloading by means of flange connections, it is recommended to have a means to seal (e.g. a sealable bolt) the flange of the screw connections.


### Dry disconnect couplings

Dry disconnect couplings may be used, only fitted as a third closure, for gases coupleable under all working conditions . If they are used, they should fulfill EN 13175: LPG equipment and accessories - Specification and testing for Liquefied Petroleum Gas (LPG) tank valves and fittings. are recommended.





Example of dry gas coupling

<b>A. LIQUIDS</b>	<b>B. GASES (liquefied flammable)</b>
<p><b><u>2.4.3 General –bottom discharge</u></b></p> <p>The leakproofness of the service equipment shall be ensured even in the event of the RTC overturning (see RID 6.8.2.2.1).</p> <p>Gaskets shall be made of a material compatible with the substance carried (see RID 6.8.2.2.1).</p> <p>Outlet valves and bottom valve operation mechanisms shall be capable of being secured and sealed.</p> <p>All parts of valves, in contact with the product, must be free of grease.</p> <p><b><u>2.5 Top Discharge</u></b></p> <p>The top connections shall, as a minimum, consist of:</p> <ul style="list-style-type: none"> <li>- Liquid phase (dip tube): DN 80</li> <li>- Vapour return: DN 50</li> </ul> <p>Both connections shall be fitted with:</p> <ul style="list-style-type: none"> <li>- a ball- or butterfly-valve and a blank flange, or</li> <li>- a dry break coupling.</li> </ul> <p>However, dry disconnect couplings should not be used on tanks of crystallisable or highly viscous substances.</p> <p>These connections should be marked with the following codes:</p> <ul style="list-style-type: none"> <li>- ORed for the liquid phase</li> <li>- Blue for the vapour return</li> </ul> <p>As additional top connection a filling nozzle with flange DN 150 is recommended.</p> <p>Other connections may be foreseen (e.g. for future fitting of an overfill protection system, temperature- or pressure gauges). Therefore an extra DN 80 flange connection is recommended. Where blind flanges, which are not preceded by a valve, are fitted on filling or discharging devices, the blind flanges shall be equipped with splash rings.</p> <p>If reasonable, inadequate spacing (approximately 140 mm) should be foreseen to connect future couplings onto the top valves (e.g. dry disconnect couplings)</p> <p><b><u>2.6 Thermometers/manometers</u></b></p> <p>Thermometers/manometers shall not be fitted except when specifically requested by the customer.</p>	<p><b><u>2.4.3 General Bottom discharge</u></b></p> <p>The leakproofness of the service equipment shall be ensured even in the event of the RTC overturning (see RID 6.8.2.2.1).</p> <p>Gaskets shall be made of a material compatible with the substance carried (see RID 6.8.2.2.1).</p> <p>Outlet valves and bottom valve operation mechanisms shall be capable of being secured and sealed.</p> <p>All parts of valves, in contact with the product, must be free of grease.</p> <p><b><u>2.5 Top Discharge</u></b></p> <p>Not applicable</p> <p><b><u>2.6 Thermometers/manometers</u></b></p> <p>See RID requirements in RID 6.8.3.2.2</p>

A. LIQUIDS	B. GASES (liquefied flammable)
<p><b><u>2.7 Controlled ventilation valves (Auto vent system)</u></b></p> <p>The RTC may be equipped with an auto vent valve, which opens simultaneously, or preferably before the bottom valve is opened. The system may be of a mechanic and/or hydraulic design.</p> <p>The auto vent valve (“Zwangselüftungsventil”) shall be connected onto a branch pipe with a diameter of not less than 50 mm, which extends from the top to the bottom of the tank. This vapour return line shall, at the bottom, be connected with a T-line which is fitted, on both sides of the RTC, with a blind flange DN 80 or a quick coupling with blind cap. A vacuum relief valve, fitted directly on the vapour line, may also be fitted to prevent implosion during discharge.</p> <p>For existing RTCs, the use of an external reinforcement ring, as a vapour line, on the tank is not recommended . If it is used, a special attention must be paid to the compatibility between the material of the line and the vapour. For new RTCs a separate return line has to be installed.</p> <p>It is recommended that vapour return lines are fitted with a device preventing liquids from entering the vapour return line.</p> <p>It must be clearly displayed (e.g. with white stripe or in writing) that an auto vent system is installed and active.</p>  <p>For RTC’s which are equipped with vapour return lines, which are not (yet) connected onto an auto vent valve, a clear indication near the vapour return</p>	<p>Thermometers/manometers shall not be fitted.</p> <p><b><u>2.7 Controlled ventilation valves (Auto vent system)</u></b></p> <p>Not applicable</p>

<b>A. LIQUIDS</b>	<b>B. GASES (liquefied flammable)</b>
<p>line must show that it is out of use.</p> <p><b>3. WALKWAYS/PLATFORMS</b></p> <p>There are no specific requirements in RID.</p> <p>At least one walkway/platform of ‘anti-slip safety grating’ construction and a kick plate shall be provided on top of the tank to give safe access to the equipment and fittings.</p> <p>The platform must cover the workplace around domes and connection points, if reasonable, and guarantee access to valves, connections, etc.</p> <p>The construction shall comply with EN 12561-7:2011.</p> <p>To mitigate the risks caused by electric overhead contact wires, new RTCs without ladders (for reaching top platforms) should be considered..</p> <p><b>4. HEATING/ INSULATION</b></p> <p>See RID requirements in RID 6.8.2.1.25.</p> <p>For RTC’s carrying products which may require heating (e.g. with a high freezing point or high viscosity), the tank, outlet line and bottom valve shall be insulated and heatable. Consideration should be given to indirectly heat the bottom valve by making use of the external heating coils of the tank.</p> <p>The vapour return line shall be insulated or integrated into the tank insulation.</p> <p>The recommended type of insulation is 100 mm thick standard insulation (Rockwool, glasswool or equivalent). The insulation must be of such material that it cannot react dangerously with the chemicals to be carried.</p> <p>Preferably, only external heating coils shall be used.</p> <p>The maximum working pressure of the heating system must be clearly indicated on the RTC.</p> <p>When multiple heating systems are fitted, the inlet connections of each circuit must be clearly marked with the name of the circuit.</p> <p>Inlet and outlet heating pipes shall be fitted with a</p>	<p><b>3. WALKWAYS/PLATFORMS</b></p> <p>Not applicable</p> <p><b>4. SUNSHIELDS</b></p> <p>See RID requirements in RID 6.8.3.2.14</p> <p>The pressure rating of gas tanks depends on whether or not thermal insulation (sun shield) is provided.</p> <p>The minimum test pressure for multipurpose LPG-type cars is:</p> <ul style="list-style-type: none"> <li>- 2.5 MPa (25 bar) for tanks with sunshields;</li> <li>- 2.7 MPa (27 bar) for tanks without sunshields.</li> </ul> <p>The disadvantages of sunshields are:</p> <ul style="list-style-type: none"> <li>- risk of coming loose and causing an accident;</li> <li>- maintenance, risk of corrosion under sunshield which is not readily visible;</li> <li>- maintenance costs, need to remove shields for inspection, painting;</li> <li>- in case of fire, it is more difficult to cool the tank.</li> </ul> <p>The advantages of sunshields are:</p> <ul style="list-style-type: none"> <li>- cost of new built is a little lower (lower steel thickness of tank);</li> <li>- the tare weight is 200-300 kg lower because the thickness of the steel is lower (for C3-hydrocarbons RTC’s the design pressure without sunshield is 2 bar higher , no difference for C4-hydrocarbons RTC’s).</li> </ul>

<b>A. LIQUIDS</b>	<b>B. GASES (liquefied flammable)</b>
<p>closing valve in compliance with EN 12561-8:2011.</p> <p><b>5. UNDERFRAME</b></p> <p>All RTC's must have shunting hooks and shall have lashing devices to be suitable for rail-ferry traffic.</p> <p>Both wagon ends should have a platform (for shunters) with handgrip. The platform can be a crossover platform or a simple step on platform.</p> <p>Axle load, arc radius and axle distance are limited for certain customers and must be agreed upon before delivery.</p> <p><b>6. EXTERNAL PAINTING/CLADDING</b></p> <p>Durable external painting is required for carbon steel RTC's, which are not insulated.</p> <p>It is recommended to clad insulated tanks with stainless steel cladding, at least around discharge connections and the area underneath. All joints in the cladding shall be weather-proofed with a suitable seal to prevent the ingress of water into the insulation. Insulated carbon steel tanks shall be painted under the insulation to avoid corrosion. Measures must be taken to prevent accumulating condensation within the insulation. Aluminium cladding is not acceptable around discharge connections and the area underneath.</p> <p><b>7. PLACARDING AND MARKING</b></p> <p>See RID requirements in RID 6.8.2.5.2. For the placards (large danger labels) mounting plates are recommended. For the orange-coloured plate marking steel frames to hold the plates shall be provided at both sides of the RTC. It is recommended using steel orange-coloured plates with figures which remain legible after 15 minutes engulfment in fire. For product dedicated RTC's, the name of the substance carried or name of a group of substances, for the carriage of which the tank has been approved, shall be inscribed on each side of the tank or on a panel.</p> <p>For marking on freight wagons see EN 15877-1:2012.</p>	<p><b>5. UNDERFRAME</b></p> <p>All RTC's must have shunting hooks and shall have lashing devices to be suitable for rail-ferry traffic.</p> <p>Both wagon ends should have a platform (for shunters) with handgrip. The platform can be a crossover platform or a simple step on platform</p> <p>Axle load, arc radius and axle distance are limited for certain customers and must be agreed upon before delivery.</p> <p><b>6. EXTERNAL PAINTING/CLADDING</b></p> <p>Durable external painting is required.</p> <p><b>7. PLACARDING AND MARKING</b></p> <p>See RID requirements in RID 6.8.3.5. For the placards (large danger labels) mounting plates are recommended. For the orange-coloured plate marking steel frames to hold the plates shall be provided at both sides of the RTC. Steel swing panels with the orange-coloured plates painted on it may also be used. It is however recommended to use steel orange-coloured plates with figures which remain legible after 15 minutes engulfment in fire. The name of the substance carried, for the carriage of which the tank has been approved, shall be inscribed on each side of the tank or on a panel. Swing panels shall be lockable and sealable.</p> <p>For marking on freight wagons see EN 15877-1:2012.</p>

A. LIQUIDS	B. GASES (liquefied flammable)
<p><b>8. END PROTECTION</b></p> <p><u>Buffer override protection</u></p> <p>See RID requirements in 6.8.4, in particular special provisions TE25.</p> <p><u>Crash buffers</u> See RID requirements in 6.8.4 in particular special provision TE22.</p> <p><a href="#">Crash buffers can help to reduce the consequences in cases of accidents</a></p>  <p><b>9. TESTING, INSPECTION AND CERTIFICATION</b></p> <p>See RID requirements in 6.8.2.4</p> <p>Companies may require more frequent inspections depending on the nature of the product e.g. risk of polymerisation.</p> <p>The RTC owner must submit test certificates to the lessee.</p> <p>Prior to putting into service, the lessor of the RTC shall carry out a technical and cleanliness inspection of the RTC <a href="#">including a leak proof test</a>.</p> <p>The required cleanliness shall be defined by means of a national or international recognised “cleanliness Key” (e.g. UIP “Reinheitsschlüssel”).</p>	<p><b>8. END PROTECTION</b></p> <p><u>Buffer override protection</u></p> <p>See RID requirements in 6.8.4, in particular special provision TE25.</p> <p>Buffer override protection or an alternative head protection is recommended, if justified and feasible.</p> <p><u>Crash buffers</u> See RID requirements in 6.8.4 in particular special provision TE22.</p> <p><a href="#">Crash buffers can help to reduce the consequences in cases of accidents</a></p>  <p><b>9. TESTING, INSPECTION AND CERTIFICATION</b></p> <p>See RID requirements in 6.8.2.4 and 6.8.3.4</p> <p>Initial and periodical tests and inspections of the tank must be carried out in accordance with RID 6.8.2.4 and 6.8.3.4 and EN 12972.</p> <p>The RTC owner must submit test certificates to the lessee.</p> <p>Prior to putting into service, the lessor of the RTC shall carry out a technical and cleanliness inspection of the RTC <a href="#">including a leak proof test</a> .</p> <p>The required cleanliness shall be defined by means of a national or international recognised “cleanliness Key” (e.g. UIP “Reinheitsschlüssel”).</p>

<b>A. LIQUIDS</b>	<b>B. GASES (liquefied flammable)</b>
<p><b>10. INFORMATION/DATA TO BE SUBMITTED TO THE LESSEE (CONSIGNOR) PRIOR TO PUTTING INTO USE RTC'S</b></p> <p>Up-to-date specification sheet including as a minimum:</p> <ul style="list-style-type: none"> <li>- arc radius</li> <li>- length of RTC</li> <li>- maximum axle distance</li> <li>- tare weight</li> <li>- capacity of the tank</li> <li>- allowable loading weights per loading category</li> <li>- design-, test- and working pressure</li> <li>- design temperature</li> <li>- maximum allowable underpressure</li> <li>- material of tank shell</li> <li>- working- and test pressure of heating</li> <li>- type of connections including type of valves</li> <li>- auto vent system</li> <li>- special features</li> <li>- type of gaskets fitted.</li> </ul> <p>Further information required:</p> <ul style="list-style-type: none"> <li>- construction year of the RTC</li> <li>- last inspection/revision and test date of tank and underframe</li> <li>- UIP cleanliness key.</li> </ul>	<p><b>10. INFORMATION/DATA TO BE SUBMITTED TO THE LESSEE (CONSIGNOR) PRIOR TO PUTTING INTO USE RTC'S</b></p> <p>Up-to-date specification sheet including as a minimum:</p> <ul style="list-style-type: none"> <li>- arc radius</li> <li>- length of RTC</li> <li>- maximum axle distance</li> <li>- tare weight</li> <li>- capacity of the tank</li> <li>- allowable loading weights per loading category</li> <li>- design- and test-pressure</li> <li>- design temperature</li> <li>- maximum allowable underpressure</li> <li>- material of tank shell</li> <li>- type of connections including type of valves</li> <li>- special features</li> <li>- type of gaskets fitted.</li> </ul> <p>Further information required:</p> <ul style="list-style-type: none"> <li>- construction year of the RTC</li> <li>- last inspection/revision and test date of tank and underframe</li> <li>- UIP cleanliness key.</li> </ul>